



**RotoSolutions Test Report
and
Qualification Notice
05/28/2021**

Product: 95 Gallon Recycled Overpack

Manufacturer and Testing Facility RotoSolutions, Inc., 1401 Jacobson Avenue, Ashland Ohio 44805

Regulation: United Nations General Recommendation on Packing for Transportation of Dangerous Goods, 49 CFR 173.3

Drum Unit Tested:	Leak Proofness	Drum 1	05212104	Drum 2	05212105	Drum 3	05212106
	Base Drop	Drum 1	05212107	Drum 2	05212108	Drum 3	05212109
	Stack	Drum 1	05212107	Drum 2	05212108	Drum 3	05212109
	Diag. Lid Drop	Drum 1	05212107	Drum 2	05212108	Drum 3	05212109

Objective: To determine the compliance with the applicable regulations for UN 1H2 container for Packing Group I solid material and 49 CFR 173.3 Salvage drum applications.

Items Tested: One Sample of lot of removable top, open head plastic container. Volumetric capacity of the container is 95 gallons. Material of construction is Linear Low Density Polyethylene (LLDPE) resin, rotationally molded.

TEST	REGULATION	DESCRIPTION	PERFORMANCE
Drop	UN 6.1.5.3 49 CFR 178.603	1.2 meter, 345 KG -18 Celsius. Unit filled with a mixture of sand and vermiculite	Passed
Stacking	UN 6.1.5.6 49 CFR 178.606	3 meters, 690 kg load 24 hours, with a mixture of sand and vermiculite	Passed
Leakproof	UN 6.1.5.4 49 CFR 173.3 (c)(1)	20 kPa 5 minutes	Passed

Conclusion: Part design complies and passes all required testing as called out in the above mentioned regulations. This unit is therefore certified. Unit must be filed and used in accordance with all pertinent DOT and UN regulations. Failure to do so renders the qualification invalid and voids all warranties implied or stated.

Load measured with scale calibrated and maintained by Ashland Scale. Temperature recorded with Amprobe IR608A Infrared Thermometer

Levels Measured with a verified Johnson angle finder. Air pressure measured with a verified Noshok pressure gauge.

Packaging Markings:



1H2\Y345\S\21\USA\M5904

Approved By:

 *Ralph Kirkpatrick*

Ralph Kirkpatrick, V.P. of Sales, 05/28/2021