



# Ultra-Containment Berm<sup>®</sup> Comparison Guide



Description (Click for more information)	Cost	Drive-in/out	Set-up Required (beyond initial deployment)	Standard Height	Other Heights Available	Standard Material	Other Materials Available
<a href="#">Collapsible Wall Model</a>	\$	-	Yes	12"	18", 24"	Copolymer-2000	PVC, XR5, Urethane
<a href="#">Compact Model</a>	\$\$\$	-	Yes	12"	-	Copolymer-2000	PVC, XR5, Urethane
<a href="#">Economy Model</a>	\$	-	Yes	12"	18", 24"	Copolymer-2000	PVC, XR5, Urethane
<a href="#">Foam Wall Model</a>	\$\$	4 Sides	No	4"	2", 6"	Copolymer-2000	PVC, XR5, Urethane
<a href="#">Modular Model (Gorilla Berm)</a>	\$\$\$	4 Sides	No	6"	-	PVC 38	Copolymer-2000, XR5, Urethane
<a href="#">Rapid Rise</a>	\$\$	4 Sides	No	12"	18"	Copolymer-2000	PVC, XR5, Urethane
<a href="#">Stake Wall Model</a>	\$\$\$	4 Sides	No	12"	-	Copolymer-2000	PVC, XR5, Urethane
<a href="#">Ultimate Model</a>	\$\$	2 Sides	Only 2 Long Slides	12"	-	Copolymer-2000	PVC, XR5, Urethane
<a href="#">Containment Wall</a>	\$\$\$	-	Yes	36"	12", 24"	Polyethylene	Call
<a href="#">Mini Foam Wall Model</a>	\$	4 Sides	No	6"	-	PVC	Call

Berm Fabric Material	Weight	Thickness	Min Temp	Max Temp	Cold Crack	Tear Strength	Puncture Resistance
Copolymer-2000	30 oz/yd <sup>2</sup>	30 mils nominal	-25°F	160°F	-25°F	30 lb <sub>f</sub> nominal	50 lb <sub>f</sub> typical
Urethane	23 oz/yd <sup>2</sup>	25 mils nominal	-45°F	160°F	-45°F	58 lb <sub>f</sub> nominal	750 lb <sub>f</sub>
PVC	22 oz/yd <sup>2</sup>	24 mils nominal	-30°F	145°F	-30°F	46 lb <sub>f</sub> nominal	91 lb <sub>f</sub>
XR5	30 oz/yd <sup>2</sup>	30 mils minimum	-30°F	160°F	-30°F	55 lb <sub>f</sub> nominal	250 lb <sub>f</sub> minimum
PVC 38	24 oz/yd <sup>2</sup>	38 mil	-30°F	145°F	-30°F	224 lb Warp/133 lb Fill	70 lb minimum



Collapsible Wall



Compact



Economy



Foam Wall



Modular (Gorilla)



Rapid Rise



Stake Wall



Containment Wall



Mini Foam Wall